

PATENT COOPERATION TREATY

PCT



REC'D 13 JUN 2005

WIPO

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY
(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 002253PC	FOR FURTHER ACTION		See Form PCT/PEA/416
International application No. PCT/IL2004/000336	International filing date (day/month/year) 20.04.2004	Priority date (day/month/year) 21.04.2003	
International Patent Classification (IPC) or national classification and IPC G02B26/08, G02B26/10, B81B3/00			
Applicant ELOP ELECTRO-OPTICS INDUSTRIES LTD. et al.			
<p>1. This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 6 sheets, including this cover sheet.</p> <p>3. This report is also accompanied by ANNEXES, comprising:</p> <p>a. <input checked="" type="checkbox"/> sent to the applicant and to the International Bureau) a total of 24 sheets, as follows:</p> <p><input checked="" type="checkbox"/> sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).</p> <p><input type="checkbox"/> sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.</p> <p>b. <input type="checkbox"/> (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)) , containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).</p>			
<p>4. This report contains indications relating to the following items:</p> <p><input checked="" type="checkbox"/> Box No. I Basis of the opinion</p> <p><input checked="" type="checkbox"/> Box No. II Priority</p> <p><input type="checkbox"/> Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p><input type="checkbox"/> Box No. IV Lack of unity of invention</p> <p><input checked="" type="checkbox"/> Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</p> <p><input type="checkbox"/> Box No. VI Certain documents cited</p> <p><input type="checkbox"/> Box No. VII Certain defects in the international application</p> <p><input type="checkbox"/> Box No. VIII Certain observations on the international application</p>			
Date of submission of the demand 18.02.2005		Date of completion of this report 09.06.2005	
Name and mailing address of the International preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465		Authorized Officer von Hentig, R Telephone No. +49 89 2399-7041 	

**INTERNATIONAL PRELIMINARY REPORT
ON PATENTABILITY**

International application No..
PCT/IL2004/000336

Box No. I Basis of the report

1. With regard to the **language**, this report is based on the international application in the language in which it was filed, unless otherwise indicated under this item.
- ☐ This report is based on translations from the original language into the following language , which is the language of a translation furnished for the purposes of:
- ☐ international search (under Rules 12.3 and 23.1(b))
 - ☐ publication of the international application (under Rule 12.4)
 - ☐ international preliminary examination (under Rules 55.2 and/or 55.3)
2. With regard to the **elements*** of the international application, this report is based on *(replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report)*:

Description, Pages

1-19 received on 17.05.2005 with letter of 11.05.2005

Claims, Numbers

1-17 received on 17.05.2005 with letter of 11.05.2005

Drawings, Sheets

1, 2, 4-8 as originally filed

3 received on 18.02.2005 with letter of 15.02.2005

- ☐ a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing

3. ☒ The amendments have resulted in the cancellation of:

- ☒ the description, pages 1-19
- ☒ the claims, Nos. 1-18
- ☒ the drawings, sheets/figs 3
- ☐ the sequence listing (*specify*):
- ☐ any table(s) related to sequence listing (*specify*):

4. ☐ This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).

- ☐ the description, pages
- ☐ the claims, Nos.
- ☐ the drawings, sheets/figs
- ☐ the sequence listing (*specify*):
- ☐ any table(s) related to sequence listing (*specify*):

* If item 4 applies, some or all of these sheets may be marked "superseded."

**INTERNATIONAL PRELIMINARY REPORT
ON PATENTABILITY**

International application No.
PCT/IL2004/000336

Box No. II Priority

1. ☒ This report has been established as if no priority had been claimed due to the failure to furnish within the prescribed time limit the requested:
☒ copy of the earlier application whose priority has been claimed (Rule 66.7(a)).
☐ translation of the earlier application whose priority has been claimed (Rule 66.7(b)).
2. ☐ This report has been established as if no priority had been claimed due to the fact that the priority claim has been found invalid (Rule 64.1). Thus for the purposes of this report, the international filing date indicated above is considered to be the relevant date.
3. Additional observations, if necessary:

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes: Claims	
	No: Claims	1-17
Inventive step (IS)	Yes: Claims	
	No: Claims	1-17
Industrial applicability (IA)	Yes: Claims	1-17
	No: Claims	

2. Citations and explanations (Rule 70.7):

see separate sheet

**INTERNATIONAL PRELIMINARY
REPORT ON PATENTABILITY
(SEPARATE SHEET)**

International application No.

PCT/IL2004/000336

Reference is made to the following documents:

D1: DE 197 28 598 A (BOSCH GMBH ROBERT) 4 February 1999 (1999-02-04)

The document D7 was not cited in the international search report. A copy of the document is appended hereto.

D7: US-A-4 001 658 (FRENK HELMUTH) 4 January 1977 (1977-01-04)

1. Re Item V

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

- a. Independent claim 1 does not meet the requirements of Article 6 PCT since it is not supported over the whole area claimed. The application discloses an micro electromechanical oscillating mirror, elastically and symmetrically coupled to two pairs of symmetrically distributed masses. A solution to the equation of motion is given for specific assumptions (symmetrical distribution of masses and stiffnesses) of equation 3 (page 9 of the application) only. Any broader scope is not supported by the description.
- b. Furthermore, it may be added that claim 1 does not meet the requirements of Article 6 PCT in that the matter for which protection is sought is not clearly defined leading to a lack of novelty (see below). The claim attempts to define the subject-matter in terms of the result to be achieved, which merely amounts to a statement of the underlying problem, without providing the concrete technical features necessary for achieving this result. In particular, the wording "wherein the mass values, ... the force value, ... and the stiffness coefficients ...are selected such that..." leaves the choice of at least five parameters (two masses, one force and two stiffness values) to the reader. Hence, it remains unclear from the wording of the independent claim, how these parameters have to be chosen with respect to each other and how the parameters have to be tuned so as to obtain the desired effect. In particular, it is unclear which

structural features or further limitations arise from this not further specified selection.

- c. The present application does not meet the criteria of Article 33(1) PCT, because the subject-matter of claim 1 is not new in the sense of Article 33(2) PCT.

The document D1 discloses (the references in parentheses applying to this document) a:

Geometric waveform oscillator (figure 1, #1) comprising

- i. a plurality of masses (figure 1, #8, #9, #7), at least one of said masses comprising
 - ii. a light processing module (figure 1, #7),
 - iii. at least one force producing element (figure 1, #8, #9) coupled to at least one of said masses, said at least force producing element applying at least one force to at least one said masses; and
 - iv. a plurality of elastic elements (figure 1, #5, #6, #20, #21), said elastic elements coupling said masses (figure 1, #8, #9, #7) together, said elastic elements (figure 1, #5, #6) coupling at least one of said masses to at least one support (figure 1, #3, #4) wherein the mass values of said masses, the force value of said at least one force and the stiffness coefficients of said elastic elements, are selected such that said light processing module oscillates according to a predetermined waveform.
- d. The subject-matter of dependent claims 2 -18 is not novel in the sense of Article 33(2) PCT either since the micro mechanical torsion mirror disclosed by document D1 comprises all features recited by the independent claim and these dependent claims. In particular, the "non-sinusoidal" waveform recited by dependent claim 2 is a feature of the torsion micro mirror known from document D1 (column 3, line 5 - 20) which can be tilted about two orthogonal axes.

**WRITTEN OPINION OF THE
INTERNATIONAL SEARCHING
AUTHORITY (SEPARATE SHEET)**

International application No.

PCT/IL2004/000336

2. It might be pointed out for the sake of completeness, that basic concept of the superposition of harmonic oscillations so as to generate oscillatory motions differing from mechanical sinusoidal oscillations is already known from highly relevant document D7 (claim 1) which also puts into question novelty and the inventive step of claims 1 -18.

SCANNING MIRROR

FIELD OF THE DISCLOSED TECHNIQUE

The disclosed technique relates to optical devices in general,
5 and to a system and method to provide non-sinusoidal oscillatory motion
to a scanner, in particular.

BACKGROUND OF THE DISCLOSED TECHNIQUE

Oscillating mirrors are employed to scan objects and raster-scan
10 displays. Such a mirror is generally connected to two vibrating flexural
beams, thereby forming a single degree-of-freedom (DOF) structure,
wherein the structure has a single torsional resonance frequency. Such
scanners oscillate according to a sinusoidal waveform. The high gain (i.e.,
large compliances) which is exhibited by a second order system at its
15 natural frequency (when there is a small amount of damping), gives rise to
a significant angular deflection under a moderate sinusoidal torque.

Sinusoidal motion of the mirror reflects the light beam in a
non-uniform manner, thereby yielding non-uniform intensity and hence, a
low level of performance. It is possible to improve the scanning
20 performance, if the mirror oscillates according to a triangular waveform.
However, the value of the torque which is to be applied to the mirror in
order to provide oscillatory motion having the triangular waveform, is
approximately two orders of magnitude greater than in the case of

sinusoidal motion. In large scale applications, where large torques can be produced, it is possible to produce this additional torque. However in small scale applications, such as micro-electromechanical systems (MEMS), due to the inherently small dimensions and the limitation of the commonly used electrostatic excitation, it is much more difficult to provide the needed torque.

SUMMARY OF THE DISCLOSED TECHNIQUE

It is an object of the disclosed technique to provide a novel method and system for oscillating the mirror of a scanner according to a geometric waveform.

5 In accordance with the disclosed technique, there is thus provided a geometric-waveform oscillator for processing light. The geometric-waveform oscillator includes a plurality of masses, at least one force producing element, and a plurality of elastic elements. Each of the force producing elements is coupled with a respective one of the masses.

10 At least one of the masses includes a light processing module. Each of the force producing elements applies a force to the masses. The elastic elements couple the masses together and the masses with a respective support. The mass values of the masses, the force values of the forces, and the stiffness coefficients of the elastic elements, are selected such

15 that the light processing module oscillates according to the geometric waveform.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosed technique will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

5 Figure 1 is a schematic illustration of a scanner, constructed and operative in accordance with an embodiment of the disclosed technique;

 Figure 2 is a schematic illustration of a five degree of freedom mathematical model of a system similar to the system of Figure 1;

 Figure 3 is a schematic illustration of a
10 micro-electromechanical-based system similar to the system of Figure 1;
and

 Figure 4A is a schematic illustration of a plot of a frequency
response of the mirror of the system of Figure 3;

 Figure 4B is a schematic illustration of a plot of oscillations of the
15 mirror of the system of Figure 3 as a function of time;

 Figure 5 is a schematic illustration of a scanner, constructed and operative in accordance with another embodiment of the disclosed technique.

 Figure 6A is a schematic illustration of a packaged device
20 generally referenced 280, including a plurality of the scanners of Figure 1, constructed and operative in accordance with a further embodiment of the disclosed technique; and

Figure 6B is a schematic illustration of a broken section of a scanning MEMS of the packaged device of Figure 6A.

DETAILED DESCRIPTION OF THE EMBODIMENTS

The disclosed technique overcomes the disadvantages of the prior art by providing a multi-degree-of-freedom system, wherein one of whose elements (e.g., a mirror, a directional radiation source, a directional
5 sensor) oscillates according to a triangular waveform. The individual masses of the system, the stiffness coefficients of the elastic elements of the system, and the waveform of the force which excites the system are selected, such that the mirror oscillates according to the triangular waveform.

10 In the description herein below, the term "mass" is used to specify both a physical object and the weight of the physical object. Reference is now made to Figure 1, which is a schematic illustration of a scanner, generally referenced 100, constructed and operative in accordance with an embodiment of the disclosed technique. Scanner 100
15 includes a mirror 102, a plurality of masses 104_1 and 104_N , a plurality of masses 106_1 and 106_M , a plurality of actuators 108 and 110, beams 112, 114, 116 and 118, and supports 120 and 122. The values of the indices M and N can be either the same or different.

Beam 112 is coupled with mirror 102 and with mass 104_1 . Beam
20 114 is coupled with mirror 102 and with mass 106_1 . Masses 104_1 and 104_N are coupled there between by a plurality of beams (not shown), similar to beam 112. Masses 106_1 and 106_M are coupled there between by a plurality of beams (not shown), similar to beam 112. Beam 116 is coupled

with mass 104_N and with support 120. Beam 118 is coupled with mass 106_M and with support 122. Actuator 108 is coupled with mass 104_1 . Actuator 110 is coupled with mirror 102. In case mirror 102 is located at a geometric center of scanner 100, mirror 102 can be regarded as a center
5 mass.

Each of beams 112, 114, 116 and 118, and the beams which couple masses 104_1 and 104_N and masses 106_1 and 106_M , is made of a substantially elastic material having a stiffness coefficient k_i . Each of beams 112, 114, 116 and 118, and the beams which couple masses 104_1
10 and 104_N and masses 106_1 and 106_M , can deflect either linearly or in an angular fashion.

Each of actuators (i.e., force producing elements) 108 and 110 is a mechanical, electronic, electromechanical, electrostatic, thermodynamic, fluidic element and the like, such as an electromagnet,
15 piezoelectric crystal, electric motor, bi-metallic element, hydraulic motor, fluid impeller, and the like. One or both of actuators 108 and 110 apply forces to either one or both of mass 104_1 and mirror 102, respectively, thereby setting mirror 102, masses 104_1 and 104_N and masses 106_1 and 106_M in motion. The values of masses 104_1 and 104_N , 106_1 and 106_M , the
20 stiffness coefficients k_i of beams 112, 114, 116 and 118, and the beams which couple masses 104_1 and 104_N and masses 106_1 and 106_M , and the waveform of the forces applied by actuators 108 and 110, are selected such that mirror 102 oscillates according to a geometric (i.e.,

non-trigonometric) waveform, such as a triangular waveform (e.g., symmetric or asymmetric), non-sinusoidal waveform, square waveform, and the like. Alternatively, either one or both supports can be replaced by an actuator.

5 Reference is now made to Figure 2, which is a schematic illustration of a five DOF mathematical model of a system similar to the system of Figure 1, generally referenced 150. Mathematical model 150 includes masses 152, 154, 156, 158 and 160, springs 162, 164, 166, 168, 170 and 172, and supports 174 and 176. Each of masses 152 and 160
10 has a value m_1 . Each of masses 154 and 158 has a value m_2 . Mass 156 has a value m_3 and is similar to mirror 102 (Figure 1). The spring constant (i.e., stiffness coefficient) of each of springs 162 and 172 is referenced k_1 . The spring constant of each of springs 164 and 170 is referenced k_2 . The spring constant of each of springs 166 and 168 is referenced k_3 .

15 Spring 162 is coupled with mass 152 and with support 176. Spring 164 is coupled with masses 152 and 154. Spring 166 is coupled with masses 154 and 156. Spring 168 is coupled with masses 156 and 158. Spring 170 is coupled with masses 158 and 160. Spring 172 is coupled with mass 160 and with support 174.

20 The coordinates of masses 152, 154, 156, 158 and 160 relative to support 176, are referenced q_1 , q_2 , q_3 , q_4 , and q_5 , respectively. When masses 152, 154, 156, 158 and 160 are set in motion, forces F_1 , F_2 , F_3 , F_4 , and F_5 , respectively, act thereon.

Since mathematical model 150 is symmetric, the mode shapes (i.e., deformation shapes) thereof can be symmetric (i.e., ϕ_{sym}) and anti-symmetric (i.e., ϕ_{asym}), which are expressed by,

$$\phi_{sym} = (\beta_1, \beta_2, \beta_3, \beta_2, \beta_1)^T \quad (1)$$

5 and

$$\phi_{asym} = (\alpha_1, \alpha_2, 0, -\alpha_2, -\alpha_1)^T \quad (2)$$

where α and β are the entries in the eigenvectors or columns of the modal matrix of mathematical model 150.

The equation of motion of masses 152, 154, 156, 158 and 160

10 is,

$$\begin{bmatrix} m_1 & 0 & 0 & 0 & 0 \\ 0 & m_2 & 0 & 0 & 0 \\ 0 & 0 & m_3 & 0 & 0 \\ 0 & 0 & 0 & m_2 & 0 \\ 0 & 0 & 0 & 0 & m_1 \end{bmatrix} q'' + \begin{bmatrix} k_1 + k_2 & -k_2 & 0 & 0 & 0 \\ -k_2 & k_2 + k_3 & -k_3 & 0 & 0 \\ 0 & -k_3 & k_3 + k_3 & -k_3 & 0 \\ 0 & 0 & -k_3 & k_3 + k_2 & -k_2 \\ 0 & 0 & 0 & -k_2 & k_2 + k_1 \end{bmatrix} q = F \quad (3)$$

where the units of the variables are as follows:

m_1, m_2, m_3 , in Kg

q , in meters

15 q'' , in m/sec²

k_1, k_2, k_3 , in N/m, and

F , in Newtons

The natural frequencies ω_r , $r = 1, 2, 3, 4, 5$, of mathematical model 150 which is described by Equation 3 (i.e., the eigenvalues of Equation 3) and

the eigenvectors φ_r thereof can easily be computed. By solving the following determinants:

$$|K - (n\omega_0)^2 M| = 0 \quad (4)$$

for $n = 1, 2, 3, 4, 5$, k_1 , k_2 , k_3 , m_1 , and m_2 , can be computed in terms of m_3 .

Thus,

$$k_1 = \frac{25}{7} \omega_0^2 m_3 \quad (5)$$

$$k_2 = \frac{45}{7} \omega_0^2 m_3 \quad (6)$$

$$k_3 = \frac{15}{2} \omega_0^2 m_3 \quad (7)$$

$$m_1 = \frac{10}{7} m_3 \quad (8)$$

$$m_2 = \frac{15}{14} m_3 \quad (9)$$

where K and M are the corresponding matrices as defined in Equation 3.

It is noted that mathematical model 150 is a linear model. Equation 3 can be used to describe an angular system similar to mathematical model 150, if the units of the variables in Equation 3 are as

follows:

m_1, m_2, m_3 , in Kg-m²

q , in radians

q'' , in rad/sec²

k_1, k_2, k_3 , in N-m/rad, and

Q , in Nm

If the natural frequencies are integer multiples of the resonance frequency ω_0 , and m_3 is given, then the following modal matrix, which is independent of masses 152, 154, 156, 158 and 160 and spring constants k_1 , k_2 and k_3 , is obtained,

$$\phi = \begin{bmatrix} 1 & -3/2 & -9/4 & -1 & 1 \\ 4/3 & -1 & 1 & 2 & -4 \\ 10/7 & 0 & 5/2 & 0 & 6 \\ 4/3 & 1 & 1 & -2 & -4 \\ 1 & 3/2 & -9/4 & 1 & 1 \end{bmatrix} \quad (10)$$

It is seen that the modal matrix includes both symmetric and anti-symmetric deformation shapes (i.e., the columns of the matrix). In the anti-symmetric mode (i.e., the second and the fourth columns), mass 156 is stationary, as identified by zeros in these two columns. On the other hand, in the symmetric modes (i.e., the first, the third and the fifth columns), masses 152, 154, 156, 158 and 160 are in motion. Ordinarily, the response of mathematical model 150 depends on the excitation parameters. However, in the present case the relative motions of masses 152, 154, 156, 158 and 160 (i.e., the modes shapes of Equation 10), depend only on mass m_3 .

Reference is now made to Figures 3, 4A, and 4B. Figure 3 is a schematic illustration of a MEMS based system similar to the system of Figure 1, generally referenced 200. Figure 4A is a schematic illustration of a plot of a frequency response of the mirror of the system of Figure 3, generally referenced 220. Figure 4B is a schematic illustration of a plot of

oscillations of the mirror of the system of Figure 3 as a function of time, generally referenced 230.

System 200 includes masses 202, 204, 206 and 208, a mirror 210, a beam 212, supports 214 and 216 and an actuator 218. Beam 212 is coupled between supports 214 and 216. Masses 202, 204, 206 and 208, and mirror 210 are coupled with beam 212. Mirror 210 is located at an approximate center of beam 212. Masses 202 and 204 are located at one side of mirror 210 and masses 206 and 208 at the other side of mirror 210. Actuator 218 is coupled with mirror 210.

Each of masses 202 and 208 has a value m_1 and a mass moment of inertia j_1 . Each of masses 204 and 206 has a value m_2 and a mass moment of inertia j_2 . Mirror 210 has a mass m_3 and a mass moment of inertia j_3 . The width and length of mass 202 is a_1 , and b_1 , respectively. The width and length of mass 204 is a_2 , and b_2 , respectively. The width and length of mass 206 is a_2 , and b_2 , respectively. The width and length (i.e., geometric characteristics) of mass 208 is a_1 , and b_1 , respectively. The width and length of mirror 210 is a_3 , and b_3 , respectively. The cross section of beam 212 is a rectangle having a width t and a height h . The distance between mass 202 and support 216 is referenced L_1 . The distance between masses 202 and 204 is referenced L_2 . The distance between mass 204 and mirror 210 is referenced L_3 . The distance between mirror 210 and mass 206 is referenced L_3 . The distance between masses 206 and 208 is referenced L_2 . The distance between mass 208 and

support 214 is referenced L_1 . The stiffness coefficients of sections of beam 212 having lengths L_1 , L_2 and L_3 , are referenced k_1 , k_2 and k_3 , respectively. The footprint of system 200 is a rectangle having a width and a length of approximately $100\mu\text{m}$ and $2000\mu\text{m}$, respectively. In this case, masses

5 202, 204, 206 and 208, mirror 210 and beam 212 are part of a semiconductor laminate having a substantially uniform and small thickness (i.e., system 200 is a 2.5 dimension system).

Mathematical model 150 (Figure 2) is a relatively simple model, albeit providing only a rough estimate of the required parameters. More

10 accurate results can be obtained by applying a finite element analysis (FEA) to mathematical model 150. Following is an example of the results of a three-dimensional FEA applied to system 200. In this example, actuator 218 applies a variable force F_v to mirror 210, where

$$F_v = A_1 \cos(\omega_0 t + \gamma_1) + A_3 \cos(3\omega_0 t + \gamma_3) + A_5 \cos(5\omega_0 t + \gamma_5) \quad (11)$$

15 and where A_1 , A_3 , and A_5 designate amplitudes, and γ_1 , γ_3 , and γ_5 designate phase angles. The amplitudes A_1 , A_3 , and A_5 and phase angles γ_1 , γ_3 , and γ_5 are selected such that the amplitude of mirror 210 as a function of time, $A(t)$, follows a substantially triangular waveform expressed by,

20

$$A(t) = \frac{8A_0}{\pi^2} \sum_{n=1}^{\infty} \frac{1}{(2n-1)^2} \cos((2n-1)\omega t) = \quad (12)$$

$$\frac{8A_0}{\pi^2} \left[\frac{\cos(\omega t)}{1^2} + \frac{\cos(3\omega t)}{3^2} + \frac{\cos(5\omega t)}{5^2} + \dots \right]$$

where A_0 is the desired amplitude and ω is the fundamental frequency of the triangular waveform. With reference to Figure 4A, the resonance frequencies (i.e., the first three harmonics) of system 200 are found to be at ω_0 , $3\omega_0$, and $5\omega_0$. Plugging these three harmonics in Equation 12 yields the theoretical oscillations of mirror 210 as a function of time (i.e., curve 222 in Figure 4B). Curve 224 graphically represents the actual amplitude of mirror 210 as a function of time. It is noted that the actual waveform of mirror 210 (i.e., curve 224) correlates well with the theoretical waveform (i.e., curve 222). It is further noted with reference to Figure 4A, that the maxima of the amplitudes of mirror 210 are located at the respective first three harmonics.

The stiffness coefficients k_1 , k_2 and k_3 corresponding to sections L_1 , L_2 and L_3 , respectively of beam 212, and the mass moments of inertia j_1 , j_2 and j_3 , are computed according to well known Equations found in Timoshenko S. P. and Goodier J. N., "*Theory of Elasticity*", Third Edition, McGraw-Hill Book Co., 1970. Thus,

$$k_i = \frac{cGh^3t}{L_i} \quad i = 1,2,3 \quad (13)$$

and,

$$J_i = \frac{a_i b_i t \rho (b_i^2 + t^2)}{12} \quad (14)$$

where c is a numerical factor depending on the ratio h/t , G is the shear modulus of beam 212, t is also the thickness of each of each of masses 202, 204, 206 and 208, and mirror 210, and ρ is the density of each of

masses 202, 204, 206 and 208, and mirror 210. Since system 200 is constructed on a chip, the thickness of each of masses 202, 204, 206 and 208, and mirror 210 is substantially equal to the thickness of beam 212. Likewise, the density of each of masses 202, 204, 206 and 208, and mirror 210 is substantially equal to the density of beam 212. Equations 13, and 14 are computed while neglecting the warping function correction for estimating the torsional spring rate, as shown in Basler K., and Kollbrunner C. F., "*Torsion in Structures*", Springer Verlag, New York, 1969.

As shown in Equations 13, and 14, the stiffness coefficient k depends on h , t and L , while the mass moment of inertia depends on a , b and t . Due to redundancy of the physical dimensions, some of the parameters of system 200 have to be assumed beforehand. Assuming the following values and substituting them in equations 13 and 14,

$$j_3 = 1.8238 \times 10^{-5} \text{ Kg-}\mu\text{m}^2$$

$$h = 10\mu\text{m}$$

$$t = 15\mu\text{m}$$

$$b_1 = b_2 = 600\mu\text{m}$$

$$b_3 = 500\mu\text{m}$$

$$\rho = 2.332 \times 10^{-15} \text{ Kg}/\mu\text{m}^3, \text{ and}$$

$$G = 8.831 \times 10^4 \text{ Kg}/\mu\text{m-s}^2$$

the gaps between masses 202, 204, 206 and 208, mirror 210, and supports 214 and 216, and the width of masses 202, 204, 206 and 208, mirror 210, are calculated as follows:

$$L_1 = 44.9\mu\text{m}$$

$$L_2 = 24.9\mu\text{m}$$

$$L_3 = 21.4\mu\text{m}$$

$$a_1 = 413.5\mu\text{m}$$

$$a_2 = 210.2\mu\text{m}, \text{ and}$$

$$a_3 = 500\mu\text{m}$$

Assuming a first resonance frequency of $\omega_0 = 15$ kHz for system 200, and solving Equations 5, 6, 7, 8 and 9, the following values for the stiffness coefficients k_1 , k_2 , k_3 , corresponding to portions L_1 , L_2 , and L_3 , respectively, of beam 212, m_1 for mass moments of inertia of masses 202 and 208 and m_2 , for mass moments of inertia of masses 204 and 206 are obtained:

$$k_1 = 0.5786 \text{ N-}\mu\text{m/rad}$$

$$k_2 = 1.041 \text{ N-}\mu\text{m/rad}$$

$$k_3 = 1.215 \text{ N-}\mu\text{m/rad}$$

$$m_1 = 2.6054 \times 10^{-4} \text{ Kg-}\mu\text{m}^2, \text{ and}$$

$$m_2 = 1.9541 \times 10^{-4} \text{ Kg-}\mu\text{m}^2$$

where the mass m_3 is replaced by the mass moment of inertia j_3 .

Reference is now made to Figure 5, which is a schematic illustration of a scanner, generally referenced 240, constructed and operative in accordance with another embodiment of the disclosed technique. Scanner 240 includes a mirror 242, beams 244 and 246, supports 248 and 250, an actuator 252 and a controller 254. Actuator 252 includes electrodes 256 and 258.

Beam 244 is coupled with mirror 242 and with support 250. Beam 246 is coupled with mirror 242 and with support 248. Electrodes 256 and 258 are located on top of mirror 242. Electrodes 256 and 258 are coupled with controller 254. Mirror 242 is electrically grounded.

Controller 254 applies a voltage V_1 to electrode 256, where

$$V_1 = V_0 + A_1 \cos(\omega_0 t + \gamma_1) + A_3 \cos(3\omega_0 t + \gamma_3) + A_5 \cos(5\omega_0 t + \gamma_5) \quad (15)$$

and a voltage V_2 to electrode 258, where

$$V_2 = V_0 - [A_1 \cos(\omega_0 t + \gamma_1) + A_3 \cos(3\omega_0 t + \gamma_3) + A_5 \cos(5\omega_0 t + \gamma_5)] \quad (16)$$

where V_0 is a bias voltage, A_1 , A_3 , and A_5 designate amplitudes, and where γ_1 , γ_3 , and γ_5 designate phase angles. Mirror 242 oscillates relative to supports 248 and 250, in directions designated by arrows 260 and 262, in a substantially triangular waveform expressed by Equation 12 herein above.

Reference is now made to Figures 6A and 6B. Figure 6A is a schematic illustration of a packaged device generally referenced 280, including a plurality of the scanners of Figure 1, constructed and operative in accordance with a further embodiment of the disclosed technique.

Figure 6B is a schematic illustration of a broken section of a scanning MEMS of the packaged device of Figure 6A.

With reference to Figure 6A, packaged device 280 includes a housing 282, a plurality of electrical contacts 284, an integrated circuit (IC) 286, and a scanning MEMS 288. Each of electric contacts 284 includes a pin 290 which protrudes from a bottom side 292 of packaged device 280. Packaged device 280 can be mounted on another device (not shown) and make electric contact with this device, by pins 290. Scanning MEMS 288 is located on top of IC 286 such that electric terminals (not shown) of scanning MEMS 288 are connected to corresponding electric terminals of IC 286. Each of electric terminals 294 of IC 286 is connected to the respective electric contact 284 by a bonding wire 296.

With reference to Figure 6B, scanning MEMS 288 includes a substrate 298, a protection layer 300 and an optically transparent layer 302. Substrate 298 can be made of a semiconductor, such as silicon, gallium arsenide, and the like. Substrate 298 includes a plurality of scanners 304 similar to scanner 100 (Figure 1). Light can enter and exit each of scanning MEMS 288 through respective windows 306. Electric terminals (not shown) on a bottom side 308 of substrate 298 are connected to respective electric terminals (not shown) on a top side 310 of IC 286.

It will be appreciated by persons skilled in the art that the disclosed technique is not limited to what has been particularly shown and

described hereinabove. Rather the scope of the disclosed technique is defined only by the claims, which follow.

CLAIMS

1. Geometric-waveform oscillator for processing light, the geometric-waveform oscillator comprising:

5 a plurality of masses, at least one of said masses comprising a light processing module;

at least one force producing element coupled with at least one of said masses, said at least one force producing element applying at least one force to said at least one masses; and

10 a plurality of elastic elements, said elastic elements coupling said masses together, said elastic elements coupling said at least one masses with a respective at least one support,

15 wherein the mass values of said masses, the force value of said at least one force, and the stiffness coefficients of said elastic elements, are selected such that said light processing module oscillates according to a geometric waveform.

2. The geometric-waveform oscillator according to claim 1, wherein said geometric waveform is selected from the list consisting of:

triangular;

20 non-sinusoidal; and

square.

3. The geometric-waveform oscillator according to claim 2, wherein said triangular waveform is symmetric.

4. The geometric-waveform oscillator according to claim 2, wherein said
5 triangular waveform is asymmetric.

5. The geometric-waveform oscillator according to claim 1, wherein said light processing module reflects light.

10 6. The geometric-waveform oscillator according to claim 1, wherein said light processing module oscillates in an oscillatory motion selected from the list consisting of:

linear; and

angular.

15

7. The geometric-waveform oscillator according to claim 1, wherein said at least one force producing element is selected from the list consisting of:

mechanical;

20

electronic;

electromechanical;

electrostatic;

thermodynamic; and

fluidic element.

8. The geometric-waveform oscillator according to claim 1, wherein said
at least one force producing element is located at said at least one
5 support.

9. The geometric-waveform oscillator according to claim 1, wherein
each of said masses, said at least one force producing element, and
said elastic elements are incorporated with a microelectromechanical
10 system.

10. The geometric-waveform oscillator according to claim 1, wherein said
light processing module is located between at least two of said
masses.

11. The geometric-waveform oscillator according to claim 10, wherein
respective pairs of said at least two masses are symmetrically located
at two sides of said light processing module.

12. The geometric-waveform oscillator according to claim 10, wherein
respective pairs of said at least two masses located at two sides of
said light processing module, have substantially the same geometric
and physical characteristics.

13. The geometric-waveform oscillator according to claim 1, wherein said masses and said elastic elements are located between two of said respective at least one support.

5

14. The geometric-waveform oscillator according to claim 1, wherein the densities of said masses and said elastic elements are substantially the same.

10 15. The geometric-waveform oscillator according to claim 1, further comprising at least one damping element coupled with at least one of said at least one masses, at least one of said elastic elements, and with said respective at least one support.

15 16. Geometric-waveform oscillator, according to any of claims 1-15 substantially as described hereinabove.

17. Geometric-waveform oscillator, according to any of claims 1-15 substantially as illustrated in any of the drawings.

20

3/8

